



- parabolik, dıştan dişli, tek taraflı
- Doğal kauçuk 45°, 55°, 70° Shore
- Talep üzerine diğer basınç kuvvetleri, boyutlar, diş uzunlukları ve kauçuk bileşikleri

Boyutlar					Yay Sertliği			Yüklemeler			Art.-Nr.
					sert	orta	yumuşak	sert	orta	yumuşak	
d mm	h mm	g mm	l mm	s mm	Sz N/mm	Sz N/mm	Sz N/mm	Fz N	Fz N	Fz N	
15	15	4	12	2	5	5	5	200	100	50	600070
18	15	6	18	2	5	5	5	300	200	100	600154
20	10	6	18	2	4	4	4	300	200	100	600155
20	15	6	18	2	5	5	5	400	200	100	600156
20	24	6	18	2	14	14	14	1000	500	250	600007
25	15	6	18	2	5	5	5	960	480	240	600038
25	19	6	18	2	8	8	8	1800	900	450	600105
25	25	6	18	2	12	12	12	2000	1000	500	600157
30	30	8	23	2	15	15	15	2600	1300	650	600158
30	36	8	23	2	15	15	15	1500	750	375	600018
32	36	8	23	2	15	15	15	1600	800	400	600025
36	40	8	23	2,5	20	20	20	4800	2400	1200	600159
50	50	10	28	2,5	25	25	25	6000	3000	1500	600160
50	58	10	28	2,5	30	30	30	6000	3000	1500	600014
50	61	10	28	2,5	30	30	30	4800	2800	1400	600030
50	65	10	28	2,5	30	30	30	6000	3000	1500	600062
50	67	10	28	2,5	30	30	30	6400	3200	1600	600161
60	75	10	28	2,5	30	30	30	5000	2500	1250	600023
72	58	12	37	2,5	25	25	25	10000	5000	2500	600162
75	89	12	37	2,5	50	50	50	16000	8000	4000	600011
76	85	16	42	2,5	40	40	40	18000	9000	4500	600163
95	83	16	42	2,5	35	35	35	14000	7000	3500	600035
115	136	16	42	2,5	80	80	80	30000	15000	7500	600008