



- her iki tarafta dıştan dişli, belden bağlamalı
- Doğal kauçuk 45°, 55°, 70° Shore
- Talep üzerine diğer basınç kuvvetleri, boyutlar, diş uzunlukları ve kauçuk bileşikleri

Boyutlar					Yay Sertliği			Yüklemeler			Art.-Nr.
					sert	orta	yumuşak	sert	orta	yumuşak	
d mm	h mm	g mm	l mm	s mm	Cz N/mm	Cz N/mm	Cz N/mm	Fz N	Fz N	Fz N	
10	15	4	10	2	33	19	11	53	31	18	800144
15	15	4	10	2	133	71	31	253	135	59	800145
15	30	4	12	2	31	23	16	96	71	50	800146
20	15	6	18	2,5	331	177	111	530	283	178	800017
25	20	6	18	2,5	389	202	111	1128	586	322	800005
30	15	8	23	2,5	740	427	270	2220	1281	810	800109
30	20	8	23	2,5	413	212	144	1487	763	518	800026
30	25	8	23	2,5	260	145	87	1040	580	348	800082
30	30	8	23	2,5	106	59	35	530	295	176	800113
30	40	8	23	2,5	115	55	32	736	352	205	800072
40	30	8	23	2,5	329	202	124	1809	1111	682	800032
40	48	8	23	2,5	162	101	57	1004	626	354	800056
40	50	8	23	2,5	171	97	51	1300	737	388	800147
50	30	10	28	2,5	652	351	227	2282	1229	681	800024
50	40	10	28	2,5	498	238	147	3685	1761	1088	800148
60	50	10	28	2,5	621	386	166	6831	4246	1826	800128
60	65	10	28	2,5	485	240	133	8245	4080	2261	800149
75	35	12	37	2,5	1181	602	346	7086	3612	2076	800150
75	40	12	37	2,5	807	466	291	4035	2330	1455	800010
100	75	16	42	3	950	435	238	19000	8700	4760	800055