



- her iki tarafta içten dişli, belden bağlamalı
- Doğal kauçuk 45°, 55°, 70° Shore
- Talep üzerine diğer basınç kuvvetleri, boyutlar, diş uzunlukları ve kauçuk bileşikleri

Boyutlar					Yay Sertliği			Yüklemeler			Art.-Nr.
					sert	orta	yumuşak	sert	orta	yumuşak	
d mm	h mm	g mm	l1 mm	s mm	Cz N/mm	Cz N/mm	Cz N/mm	Fz N	Fz N	Fz N	
10	15	4	4	2	82	40	27	99	48	33	800042
15	15	4	4	2	199	111	72	219	122	79	800140
15	30	4	12	2	45	36	17	106	83	39	800166
20	15	6	6	2,5	441	227	168	441	227	168	800106
25	20	6	6	2,5	419	251	142	838	502	284	800167
30	15	8	8	2,5	815	490	337	1223	735	506	800168
30	20	8	8	2,5	457	252	141	914	504	282	800060
30	25	8	8	2,5	431	199	131	991	458	301	800077
30	30	8	8	2,5	150	68	47	525	238	165	800169
30	40	8	8	2,5	125	65	35	675	351	189	800170
40	30	8	8	2,5	355	199	102	1420	796	408	800143
40	48	8	8	2,5	188	111	67	940	555	335	800097
40	50	8	8	2,5	183	101	64	1226	677	429	800171
50	30	10	10	2,5	921	499	375	1842	998	750	800126
50	40	10	10	2,5	530	206	147	2544	989	706	800172
60	50	10	10	2,5	701	389	177	6309	3501	1593	800173
60	65	10	10	2,5	417	199	127	5421	2587	1651	800174
75	35	12	12	2,5	1876	978	556	7504	3912	2224	800175
75	40	12	12	2,5	1058	597	364	3597	2030	1238	800047
100	75	16	16	3	827	403	291	14886	7254	5238	800176